


BT SMART TOWER 3000 IP24 CE



SPEC

- 1) Voltage : 230~240V
- 2) Wattage : 3000W \pm 5%
- 3) Lamp Color Temperature (Coated) : 1600 \pm 200K
- 4) Total Weight : 8.5Kg


WORKING CONDITION

- 1) Burning Position : Within Vertical \pm 5°
- 2) Burning Cycle : Continuous or Intermittent
- 3) Burning Voltage : MAX 240V
- 4) Frequency : 50/60 Hz


LIFE

- 1) Life time : 5,000 hour (Normal Condition)

Modification			
No.	Description	Date	Remark



NO	ITEM	MATERIAL	Q'TY	SPEC
1	Body	Aluminum (AL 6063)	1	t=2.0
2	Lamp	Quartz	2	230V 1500W
3	Refector	Aluminum (AL SB#1050)	2	T=0.5
4	Safety grill	Stainless steel (SUS #201)	2	Φ 1.55 Cr Plating
5	Electric wire	SILICON (E-012)	1	3core x 1.5mm ² x 2m x plug

TITLE : BT SMART TOWER 3000 IP24			NO	DESCRIPTION	MAT'L	FINISH	Q'TY	REMARK
THIRD ANGLE		UNIT : mm						
PROJECTION		SCALE : FREE						
DRAWN		CHECKED	APPROVED	도면에 지정되지 않은 일반공차				
SH.LEE					정밀급	보통급	거친급	기준치수(mm)
					±0.05	±0.10	±0.20	0.5이상 6이하
					±0.10	±0.20	±0.50	6초과 30이하
					±0.15	±0.30	±0.80	30초과 120이하
					±0.20	±0.50	±1.20	120초과 315이하
 HANA CO.,LTD					±0.30	±0.80	±2.00	315초과 1000이하
					±0.50	±1.20	±3.00	1000초과 2000이하